



AH 710 - AH 780

Back filter exhaust grilles

Product	AH 710	AH 780
Construction material	Aluminium	Aluminium
Finishing	Natural anodized	Natural anodized

AH 710 and AH 780 back filter exhaust grilles are made as follows:

- **AH 710**
extruded aluminium frame.
Fixed horizontal profiled vanes, anodized, 40° bent. Extruded aluminium frame for 23 mm thick filter. Front part hinged to frame.
- **AH 780**
extruded anodized aluminium frame.
Central aluminium square grid 12.5 x 12.5 mm.
Extruded aluminium frame for 23 mm thick filter. Front part hinged to frame.

Applications AH 710 and AH 780 grilles are especially used in residential, civil and light commercial systems. They allow for quick and easy maintenance operations.

Installation They are installed from the inside of the frame, hence no screws are visible, and this contributes to enhancing the esthetical appearance of the installation, which can be vertical on the wall or horizontal in false ceilings.

Sizes (mm)		Filter PFE thickness 23 mm Classe G3	Sizes (mm)	
L	H		L 1	H 1
400 x 200			395 x 195	
500 x 200			495 x 195	
600 x 200			595 x 195	
800 x 200			795 x 195	
300 x 300			295 x 295	
400 x 300			395 x 295	
500 x 300			495 x 295	
600 x 300			595 x 287	
800 x 300			795 x 295	
400 x 400			395 x 395	
500 x 400			495 x 395	
600 x 400			595 x 395	
800 x 400			795 x 395	
500 x 500			495 x 495	
800 x 500			795 x 495	
560 x 560			555 x 555	
600 x 500			595 x 495	
600 x 600			595 x 595	

Overall dimensions 600X600 (for installation in the false ceiling overhanging mounted)

Quick selection

The air flow rates and the pressure drop rates are certified according to the UNI 8728 and prEN 12238 standards, by an independent and certified body, in compliance with the legislation in force on energy saving standards.

	Q min.	Q max
NR	< 25	< 35
Pressure drop Pa	< 5	< 25

Size

