



GT 015

Adjusting dampers, 150 mm pitch

| | |
|-----------------------|-------------------------|
| Product | GT 015 |
| Construction material | Steel |
| Finishing | Electrolytic galvanized |

GT 015 dampers are used to accurately adjust and control the air flow and the air pressure in conditioning and ventilation systems and in air treatment plants. The dampers have electrolytic galvanized

steel finishing; U-shaped frame; opposite veneered blades operated from outside. The pins are made of galvanized steel (12 mm diameter) and are located in nylon bushes.

The dampers have an aluminium side gasket that provide a quite good tightness of the closed damper. A projecting 100 mm pin control is used for manual or motor adjusting operations.

| Height (mm) H | 200 | 300 | 400 | 500 | 600 | 700 | 800 | 900 | 1000 | 1100 | 1200 | 1300 | 1400 | 1500 | 1600 | 1700 | 1800 | 1900 | 2000 |
|------------------|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|------|------|------|------|
| 310 | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| 460 | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| 610 | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| 760 | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| 910 | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| 1060 | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| 1210 | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| 1360 | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| 1510 | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| 1660 | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| 1810 | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| 1960 | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |

Special type

- GT 016 type with stainless steel pins and bronze bushes (25% increase)
- GT I 015 stainless steel AISI 304 or 316 type (prices at request)
- GT P 015 type with parallel blade type

For duct mounted counter frame see technical sheet: WR 002
For wall mounted counter frame see technical sheet: WR 003
For manual controls and electric actuators see technical sheet:
"Accessories for adjusting dampers"

Specify W x H in the order.

Size

